

Lift Table & Access Lift



“U” Low Lift Table **HU** series

- “U” shaped top platform.
- “U” shaped table are specially for handling pallets, no need for a pit or load.
- They are manufactured to all European safety standards including EN1570:1999.
- Remote power pack with pedestal and controls, protected to IP54.
- Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- 24V control box with UP and DOWN buttons and emergency stop.
- External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed.
- Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- Removable lifting eyes to facilitate handling and installation of the lift table.
- Oilless bushings on pivot points.
- Quick assembly joint for oil hose.



Model		HU600	HU1000	HU1500
Capacity	(kg)	600	1000	1500
Max. Height	H (mm)	860	860	860
Collapsed Height	h (mm)	85	85	105
Platform	LxW (mm)	1450x985	1450x1140	1600x1180
Lift Time	(sec)	25~35	25~35	30~40
Power Pack		380V/50Hz, AC1.1kw	380V/50Hz, AC0.75kw	380V/50Hz, AC1.5kw
Net Weight	(kg)	207	280	380

Note: Clearance between two forks for pallet truck access 585mm.

Low Profile Lift Table **HY** series

- Heavy duty design with larger platform.
- These tables achieve a low closed height, eliminating the need for a pit installation.
- They are manufactured to all European safety standards including EN1570:1999.
- Remote power pack with pedestal and controls, protected to IP54.
- Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- 24V control box with UP and DOWN buttons and emergency stop.
- External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- Removable lifting eyes to facilitate handling and installation of the lift table.
- Oilless bushings on pivot points.
- Loading ramp is a standard equipment.



Model	Capacity (kg)	Platform Size LXW(mm)	Min. Height (mm)	Max. Height (mm)	Stroke (mm)	Lifting Time (second)	Power Pack	Net Weight (kg)
HY1001	1000	1450×1140	85	860	775	25	380V/50HZ,AC 0.75kw	357
HY1002	1000	1600×1140	85	860	775	25	380V/50HZ,AC 0.75kw	364
HY1003	1000	1450×800	85	860	775	25	380V/50HZ,AC 0.75kw	326
HY1004	1000	1600×800	85	860	775	25	380V/50HZ,AC 0.75kw	332
HY1005	1000	1600×1000	85	860	775	25	380V/50HZ,AC 0.75kw	352
HY1501	1500	1600×800	105	870	775	30	380V/50HZ,AC 1.5kw	367
HY1502	1500	1600×1000	105	870	775	30	380V/50HZ,AC 1.5kw	401
HY1503	1500	1600×1200	105	870	775	30	380V/50HZ,AC 1.5kw	415
HY2001	2000	1600×1200	105	870	775	35	380V/50HZ,AC 2.2kw	419
HY2002	2000	1600×1000	105	870	775	35	380V/50HZ,AC 2.2kw	405